

Litum Thinner No. 17

Description

This is a paint thinner. Designed to improve the flow of a range of Litum epoxy products. Can also be used as cleaner for pumps and tools before and after painting.

Typical use

Recommended usage as per technical datasheet or application guide for the specific product to be applied.

When thinners are used as a cleaning solvent, the use must be in accordance with prevailing local regulations.

Colors

Clear

Product data

Solids by volume	0%
Flash point (ISO 3679 Method 1)	25°C
Density	0.86±0.01 kg/l
Volatile organic compounds (VOC)	868 g/l

The provided data is typical for factory-produced products.

Mixing ratio

Single pack

Packing size

	Volume (L)	Container (L)
Litum Thinner No. 17	5/20	5/20

Storage and shelf life at 23°C

Storage conditions are to keep the containers in a dry, cool, well-ventilated area and away from source of heat and ignition. Containers must be kept tightly closed. Handle with care.

Litum Thinner No. 17	48 months
-----------------------------	-----------

The above is minimum shelf life, thereafter the paint quality is subject to re-inspection.

Qualification, health and safety

This product is for professional use only. The applicators and operators shall be trained, experienced and have the capability and equipment to mix/stir and apply the coatings correctly and according to Litum's technical documentation. Applicators and operators shall use appropriate personal protection equipment when using this product. This guideline is given based on the current knowledge of the product. Any suggested deviation to suit the site conditions shall be forwarded to the responsible Litum representative for approval before commencing the work. Please observe the precautionary notices displayed on the container. Use under well-ventilated conditions. Do not inhale spray mist. Avoid skin contact. Spillage on the skin should be immediately removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

Disclaimer

The information in this document is given to the best of Litum's knowledge, based on laboratory testing and practical experience. Litum's products are considered as semi-finished goods and as such, products are often used under conditions beyond Litum's control. Litum cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Litum reserves the right to change the given data without further notice. Users should always consult Litum for specific guidance on the general suitability of this product for their needs and specific application practices. In case of any inconsistencies between two languages of this document, the Russian version will prevail.